



TECHNICAL INFORMATION

Series 150

Subject	Details	
Frame	Clear	Frameless
	Stand Alone	With Frame
Vent	Direct Vent (by Dura Vent)	
Interior Design Media	Wood Style	Log Set with Beige Embers
		Mixed Long and Short Branches with Beige Embers
	Ceramic Stones	Colors: Grey or White
		Size: Large or Small
	Glass (by others):	Crushed Glass
Pebbles		
General Note	Leave 20% of burner and grill uncovered by media	
Type of Gas	Natural Gas (NG) or Propane (LP)	
Weight	Clear 150	406 lbs., 183 kg.
	Clear 150 RS/LS	444 lbs., 200 kg.
	Clear 150 TS	444 lbs., 200 kg.
	Clear 150 Tunnel	444 lbs., 200 kg.
	Space Creator 150	444 lbs., 200 kg.
	Stand Alone 150	444 lbs., 200 kg.
Standard	Safety	ANSI Z21-88-2009-CSA 2.33-2009
	Efficiency	ANSI P.4.1-09
Operation	Remote Control, full automatic (wall control unit is optional)	



Product Specifications

The appliance has been certified for use with either Natural Gas (NG) or Propane Gas (LP), and NOT for use with solid fuels.

These appliances are approved for indoor use. For indoor installation they must be installed maintaining required clearances. Refer to manual for clearance distances. Installation is recommended in living spaces such as bedrooms, living rooms, great rooms, etc. The appliance is not approved for closet installation.

The appliance must be properly connected to a venting system.

The appliance must be installed according Ortal USA requirements in addition to any local codes that may apply. If none exist then the current CSA installation code must be followed:

- USA, ANSI Z223.1/NFPA 54
- Canada, CSA B149

Gas Pressures & Power Output

Models Burner Series 150	Gas	Inlet Pressures		Manifold Pressures		Power output	
		Min.	Max.	Min.	Max.	Min.	Max.
Clear 150 Clear 150RS Clear 150LS Clear 150TS Clear 150 Tunnel Space Creator 150 Stand Alone 150	Natural Gas (NG)	7.0"	7.0"	0.9"	3.5"	23,300	43,700
		WC	WC	WC	WC	BTU/hr	BTU/hr
	Propane (LP)	1.74	1.74	0.22	.87	6.83	12.81
		kPa	kPa	kPa	kPa	kW	kW
	Propane (LP)	11.0"	11.0"	5.8"	10.7"	27,100	36,900
		WC	WC	WC	WC	BTU/hr	BTU/hr
		2.73	2.73	1.44	2.66	7.95	10.8
		kPa	kPa	kPa	kPa	kW	kW

Parts Included:

- Ortal fireplace box
- Ortal burner (sizes vary based on fireplace selection)
- Mertix GV60 combination control valve, Mertix Maxitrol GV60 ignition and control system (wireless remote control with battery and receiver)
- Spark/pilot/thermal coupling unit
- Rutland silicon product for RS/LS/TS and Space Creator models,
- glass removal tool (glass suction cups and 10mm wrench)
- 4 leg extensions
- 1 restrictor set (not applicable for Space Creator models).